



Last Rev Date: 10/01/2013

Physical Properties

Appearance Fabric	Maximum VOS 0 lbs/gal	Trapezoidal Tear Strength 18.5 lbs (ASTM D-2263)
Color White polyester	Tensile Strength Film (Initial) 44 lbs/inch (ASTM D-1628)	Weight Of Fabric 1.5 oz/sq. yd. (ASTM D-1117)
Maximum VOC 0 g/l		

Approvals and Certifications

Complies with ASTM D-1688-80, Type III.

Description

HE296 - ELASTO TAPE REPAIR FABRIC is a heat set, lightweight, 100% spunbonded polyester, non-woven mat for use with **HE289 ElastoCaulk** and other Henry asphaltic mastics and coatings. It has a high degree of fabric impregnability, tensile strength, expansion behavior, puncture resistance, tongue tear strength, and tear strength. Excellent repair fabric for both new and old construction in roofing and waterproofing applications.

Usage

To reinforce repair and flashing mastics such as **Henry HE289 ElastoCaulk, HE204 Plastic Roof Cement, HE208 Wet Patch Roof Cement**, and **HE209 ElastoMastic**.

Features:

- 20x10 thread count for tensile strength
- Will not rot or decay
- Convenient 4" width for small repairs

Additional Physical Properties:

Grab Tensile:

- 44 lbs MD (ASTM D-1682)
- 35 lbs XMD (ASTM D-1682)

Elongation:

- 52% MD (ASTM D-1682)
- 53% XMD (ASTM D-1682)

Trapezoidal Tear Strength:

- 18.5 lbs (Meridian Load) MD (ASTM D-2263)
- 13.2 lbs (Meridian Load) XMD (ASTM D-2263)

Thickness.....8.7 mils

Surface Preparation

Follow the directions for use of the mastic to be used with this product.

Application

Cut **HE296 - ELASTO TAPE REPAIR FABRIC** to the appropriate length, extending approximately 3" beyond the repair area, and embed it without wrinkles or buckles into a layer of mastic approximately 1/8" thick. Apply another coat of mastic of the same thickness as embedding coat, making sure the fabric is completely covered.

Caution

Use gloves and other protective clothing when working with this material.

Employers should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

Product Sizes

4IN X 150FT ROLL (0.49 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**