

METAL FLASHING
(FOR REFERENCE ONLY - ACTUAL
CONDITIONS MAY VARY)

METAL FLASHING

FILTER FABRIC

PAVER SYSTEM OR
GRAVEL BALLAST

OPTIONAL MOISTURE
RETENTION FABRIC

WATER RETENTION
AND DRAINAGE
COMPOSITE

INSULATION

OPTIONAL
DRAINAGE
COMPOSITE

ROOT BARRIER

PUMADEQ FLEX 30SL
(80 MILS)
REINFORCED WITH
PUMADEQ N-FLEECE

PUMADEQ PRIMER 20
OR **HENRY GC PRIMER**

PREFABRICATED
EXPANSION JOINT BY
OTHERS AS SPECIFIED

18" MIN

VARIES

NOTES:

1. DETAIL SHOWS HENRY VEGETATIVE ROOFING WITH **PUMADEQ** SYSTEM WATERPROOFING ASSEMBLY WITH A REINFORCED FIELD MEMBRANE. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR AUTHORIZED SUBSTRATES.
2. DO NOT INSTALL **PUMADEQ** SYSTEM BEYOND PRIMED SURFACES.
3. DETAIL IS FOR REFERENCE ONLY. CONTACT EXPANSION JOINT MANUFACTURER FOR PROJECT SPECIFIC REQUIREMENTS.
4. EXPANSION JOINT MANUFACTURED AND INSTALLED BY OTHERS AS SPECIFIED. CONTACT HENRY FOR PROJECT SPECIFIC COORDINATION OF **PUMADEQ** SYSTEM WITH EXPANSION JOINT.
5. DEPTH OF GROWING MEDIA MAY VARY DEPENDING ON PROJECT SPECIFIC REQUIREMENTS.
6. DETAIL IS FOR REFERENCE ONLY. REFER TO DESIGN PROFESSIONAL TO VERIFY WIND UPLIFT REQUIREMENTS.
7. REFER TO THE **PUMADEQ** SYSTEM GUIDE SPECIFICATION AND WATERPROOFING DETAILS FOR RECOMMENDED INSTALLATION PROCEDURES.

Henry[®]

999 N. Pacific Coast Hwy, Suite 800
El Segundo, CA 90245
800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY[®] DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

VEGETATIVE ROOFING - PUMADEQ SYSTEM

EXPANSION JOINT
REINFORCED FIELD MEMBRANE (CSP 3-5)
PREFABRICATED EXPANSION JOINT

SCALE: N.T.S. 06-01-2020

VR-PUMA-R8B