

Name Modified Plus NP180gT4 Cap Sheet



Product ID BH180GTB Classification 07 27 00.00 Thermal and Moisture Protection (insulation water barrier): Air Barriers

Website www.henry.com

Manufacturer Henry Company Contact Name Whitney Randall
Address 999 N. Sepulveda Blvd. Title Director, Regulatory Compliance Systems
Suite 800
El Segundo, CA 90245 Phone 484-557-1247
Email wrandall@henry.com

Description ModifiedPlus® NP180gT4 Cap Sheet is used as the top ply in a two-ply roofing system and as a flashing membrane for modified bitumen roofing, conventional built-up roofing and as a maintenance repair material. NP180gT4 is used as an exposed flashing sheet in 790-11 hot rubberized asphalt systems.

Release Date 2014-05-28 Expiry Date 2017-05-28
HPD URL https://tool.hpdcollaborative.org/uploads/files/hpds/335/1213-20140528094026.pdf
Certifier Certificate #

SUMMARY DISCLOSURE

The content of this product was assessed for health hazard warnings as required using Pharos

Residuals Disclosure Full Disclosure of Intentional Ingredients
Measured 100 ppm (ideal) Measured 1000 ppm Predicted by process chemistry As per MSDS (1,000 & 10,000 ppm) Not disclosed Other
Full Disclosure of Known Hazards Disclosure Notes

Contents in Descending Order of Quantity ASPHALT , QUARTZ , LIMESTONE; CALCIUM CARBONATE

Hazards Highest concern GreenScreen score - List Translator Benchmark 1
PBT (Persistent Bioaccumulative Toxic) Cancer Gene Mutation
Development Reproductive Endocrine Respiratory
Neurotoxicity Mammal Skin or Eye Aquatic toxicity
Land toxicity Physical hazard Global warming Ozone depletion
Multiple Unknown

Total VOC Content Material (g/L) N/A Regulatory (g/L) N/A
Does the product contain exempt VOCs? Are there VOC-free tints available?

Notes

Certifications + Compliance

VOC Emissions Not tested VOC Content N/A

The HPD Standard is solely a declaration of product content and direct health hazards associated with exposure to its individual contents. It is not a full assessment of environmental impacts from the life cycle of this product. It is not an assessment of risks associated with actual use of the product. It does not address the potential health impacts of substances used or created during manufacture that do not appear in the final product as residuals, nor substances created during combustion or other degradation processes.

This Health Product Declaration was generated following the requirements of the noted Standard version and is valid for a total of three years after date of issue or three months after a substantive change of product contents occurs. Users should verify that this Health Product Declaration is compliant with the most current version of the HPD Standard. Accuracy of claims made in this Health Product Declaration is the sole responsibility of the listed manufacturer and certifier (if applicable). The HPD Collaborative does not warrant any claim made herein, explicit or implicit. The HPD Standard is an “open standard” developed and managed by the HPD Collaborative, a nonprofit organization. For more information, visit [hpdcollaborative.org](http://hpdcollaborative.org).

## CONTENT IN DESCENDING ORDER OF QUANTITY

All ingredients must be assessed for health warnings against Priority Hazard Lists, regardless of disclosure level.

Priority Hazard Lists and information on the GreenScreen Benchmarks can be found at [www.hpdcollaborative.org/hazardlists](http://www.hpdcollaborative.org/hazardlists).

**GS:** GreenScreen Benchmark; **RC:** Recycled Content, **PC:** Post Consumer, **PI:** Post Industrial (Pre-consumer), **BO:** Both; **Nano:** comprised of nanoscale particles or nanotechnology

Name	CAS RN	% weight	GS	RC	Nano	Role
Hazard A	Warning A					
Hazard B	Warning B					
Hazard C	Warning C					
Hazard D	Warning D					
Hazard E	Warning E					
Notes						
<b>ASPHALT</b>	8052-42-4	40 - 60 %	LT-1	N	N	waterproofing, flexibility
CANCER	NIOSH-C: Occupational carcinogen (also in MAK, IARC, NTP-RoC)					
PBT	WA PBT: PBT					
Asphalt present in a sheet-applied membrane and is not heated or melted during application						
<b>QUARTZ</b>	14808-60-7	10 - 20 %	LT-1	N	N	Filler
CANCER	IARC: Group 1: Agent is carcinogenic to humans - inhaled from occupational sources (also in NIOSH-C, MAK, NTP-RoC, Prop 65)					
This material is encapsulated in the system and is not expected to be released during use.						
<b>LIMESTONE; CALCIUM CARBONATE</b>	1317-65-3	10 - 20 %	LT-U	N	N	Filler
None found	No warnings found on HPD Priority lists					

## CERTIFICATIONS AND COMPLIANCE

**Certifying Party** = First: Manufacturer’s self-declaration; Second: Verification by trade association or other interested party; Third: Verification by independent certifier (ideal).

**Applicable facilities** = Manufacturing sites to which testing applies.

Type	Standard or Certification			Certifier or Laboratory
	Certifying Party	Issue Date	Expiry Date	Certificate URL
	Applicable Facilities			

Notes	
VOC Emissions	Not tested
VOC Content	N/A
Recycled Content	Not tested
Other	

**ACCESSORY MATERIALS**

This section is for additional products required by warranty or recommended by the manufacturer for installation (such as adhesives, fasteners, or factory coatings) or for maintenance, cleaning, or operations. Refer to Health Product Declarations, published separately, for a complete view of these products. Note: This declaration is not intended to address hazards of the installation process.

Required or Recommended Product	URL for Companion Health Product Declaration
<b>Condition when required or recommended and/or other notes</b>	

**NOTES**