



NOTES:

1. DETAIL SHOWS **BLUESKIN® VP100** ASSEMBLY INSTALLED OVER EXTERIOR GRADE SHEATHING. ACCEPTABLE SUBSTRATES INCLUDE PLYWOOD, OSB, CONCRETE, GYPSUM BOARD AND CONCRETE BLOCK.
2. NO SUPPLEMENTAL DETAILING REQUIRED FOR SUBSTRATE GAPS UP TO 1/2" WIDE WHERE **BLUESKIN® VP100** IS INSTALLED CONTINUOUSLY AND MEMBRANE SEAMS EXTEND A MINIMUM OF 3" BEYOND SUBSTRATE GAPS.
3. CLADDING NOT SHOWN FOR CLARITY.
4. INSTALL THE **BLUESKIN® VP100** ASSEMBLY TO PROVIDE A CONTINUOUS AIR AND WATER BARRIER.
5. REFER TO **BLUESKIN® VP100** GUIDE SPECIFICATION FOR RECOMMENDED INSTALLATION PROCEDURES.

Henry®

999 Sepulveda Blvd., Suite 800
 El Segundo, CA 90245
 800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY® DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

BLUESKIN® VP100 SELF-ADHERED WATER RESISTIVE AIR BARRIER

CONSTRUCTION JOINTS

SUBSTRATE GAPS UP TO 1/2" WIDE
 NO SUPPLEMENTAL DETAIL REQUIRED

SCALE: N.T.S.

12-18-2017

BSVP100-8A1