



## STATIC JOINT UP TO 1"

- NOTES:
1. REFER TO THE HENRY PUMA TECHNICAL DATA SHEET FOR PRIMER SELECTION AND PROPER SUBSTRATE PREPARATION PRIOR TO INSTALLATION.
  2. THE DEPICTED DETAIL IS NOT INTENDED TO BE USED AT DYNAMIC JOINT CONDITIONS.
  3. BOND BREAKER TAPE IS INSTALLED BETWEEN THE HE925 AND AQUA-BLOC PUMA MEMBRANE
  4. HENRY 790-11 OR CM100 WATERPROOFING MEMBRANE MAY BE USED AS THE *FIELD MEMBRANE* IN THE DEPICTED DETAIL. THE REQUIRED PROTECTION COURSE FOR THE DEPICTED *FIELD MEMBRANE* IS NOT SHOWN FOR CLARITY.
  5. REFER TO THE HENRY 790-11 OR CM100 TECHNICAL DATA SHEET AND GUIDE SPECIFICATION FOR SURFACE PREPARATION AND APPLICATION INSTRUCTIONS SPECIFIC TO THE *FIELD MEMBRANE*.

**Henry**  
COMPANY

AQUA-BLOC PUMA LIQUID APPLIED FLASHING

SCALE: N.T.S.

CONCRETE DECK

03-17-17

WALL STATIC  
JOINT DETAIL

PUMA-7